

ZM 2124

6 ZONES AMPLIFIED MASTER UNIT

DESCRIPTION

ZM 2124 is the ZM 2000 system master unit that includes a preamplifier with 6 zones selection and a built-in 240 W amplifier. It is based on a dual bus architecture, where the first bus is mainly dedicated for selective / all-call paging, while the second bus is for music distribution (or other signals). Toggle buttons turn on / off the second bus (music) on each zone and logic inputs / outputs (GPI / GPO) are available to interface the system with other devices. ZM 2124 is mostly indicated for small systems, where the required power for each zone is limited. It has input connectors for audio sources, can manage priority and route the two buses to the system zones. It also includes an output level control for each of the 6 zones powered by the internal amplifier. An additional external amplifier is needed to keep the music programs to zones not involved by paging.



FEATURES

- 240 W total power
- Dual-bus system architecture
- Selectable inputs priority
- Link up to 8 ZE 2200 zone expansions
- 24 V DC secondary power supply
- Dedicated paging input (up to 6 BM 2006)
- Emergency audio input
- Auxiliary external amplifier input
- Selectable chime generator
- Dedicated wall mount remote control

TECHNICAL SPECIFICATIONS

System specifications

Number of zones managed:	54
Built-in power amplifier:	Yes
Max number of consoles:	6
Number of console buses:	1
Max number of units connectable:	9
Communication bus:	Serial
Connection Cables:	FTP CAT 5

Amplifier specifications

Number of channels:	6
Power output (@ 100 V):	240 W RMS
Frequency Response (-3dB):	50 Hz ÷ 20 kHz
Signal/noise rate ("A" weighted)	>75 dB
Distortion (THD+N) @ 1 kHz nominal power:	<1 %

Input section

Total number of inputs:	9
Balanced:	6
Unbalanced:	3
Mono:	6
Stereo:	3
Mic inputs:	2
Mic connectors:	XLR
Mic Phantom:	17.5 V DC
Line inputs:	2
Line connectors:	RCA
Mic+Line inputs:	2
Mic+Line connectors:	XLR
Mic+Line Phantom:	17.5 V DC
Paging inputs:	3
Paging connectors:	RCA, RJ45
Paging command:	Contact
General Purpose Inputs (GPI):	10
Programmable GPI:	Yes

Output section

Signal output number:	1
Signal output connectors:	XLR
Power output connectors:	Euroblock
General Purpose Outputs (GPO):	10

Processing

Tone controls:	Yes
----------------	-----

Controls

Configuration:	Front panel
Priority:	Yes
Music on hold:	Yes
Chime tone:	Yes

Protections

Cooling:	Convection
----------	------------

Power requirement	Operating voltage:	220-240/115 V~ 50/60HzV ~ Hz
	Voltage selection:	External
	DC power:	Yes
	DC power value:	24 V
	Power consumption (MAX):	720 W

Standard compliance	CE marking:	Yes
----------------------------	-------------	-----

Physical specifications	Cabinet/Case Material:	Metal
	Color:	Black
	Rack mounting:	19", 3U

Size	Height:	133 mm / 5.24 inches
	Width:	430 mm / 16.93 inches
	Depth:	365 mm / 14.37 inches
	Weight:	16.4 kg / 36.16 lbs

Shipping informations	Package Height:	296 mm / 11.65 inches
	Package Width:	490 mm / 19.29 inches
	Package Depth:	490 mm / 19.29 inches
	Package Weight:	18.8 kg / 41.45 lbs


PART NUMBER

- **12135085**

ZM 2124


EAN 8024530010232

DRAWINGS




PANELS

Front panel



Rear panel





ACCESSORIES