

The cab is roomy and comfortable, equipped with high technology analogue instrumentation.

DEUTZ-FAHR AGROTRON X 720



<u>a.</u>
4
Ė
- 07/1
'
4
316
<u>∞</u>
308.8161.3.4-2
de
Ö
Ă.
eu
ᆵ
ar
)e
200
etir
홅
Σ
Š
Б
2
20
Д

TECHNICAL DATA		AGROTRON X	
IECHNICAL DAIA		720	
NGINE		T. 2	
missions Aanufacturer		Tier 3	
Panuracturer DEUTZ Common Rail		Deutz TCD 2013 L06 4V DCR	
Cylinders/Capacity	No./cc	6/7,146	
urbo Intercooler intake	110.7 CC	•	
fax. homologated power at rated speed (2000/25/EC)	kW/hp	202/275	
ower at rated engine speed (ECE R 120)	kW/hp	198/269	
lax. engine speed (rated)	rpm	2240	
lax. torque	Nm	1035	
ectronic engine control		•	
ir filter with dust ejector		•	
quid cooling with openable radiators		•	
xhaust on cab A-post	114	• FOF	
uel tank capacity iodiesel fuel	litres %	585 B100	
OWERSHIFT GEARBOX	76	віоо	
lumber of speeds with supercreep	n°	40+40	
owershift number of speeds	n°	4	
linimum/maximum speed with supercreep	km/h	3.29/0.48	
lax. speed	km/h	50	
utomatic Powershift		•	
omfort Clutch		•	
lectrohydraulically engaged shuttle		•	
EAR PTO			
fultiplate wet clutch		•	
ectrohydraulically engaged clutch		•	
40/540ECO/1,000/1,000ECO PTO .T.O. 540/1,000		0 ●	
RONT AND REAR AXLE		•	
ront wheel drive electrohydraulically engaged		•	
teering angle/radius 4WD	degrees/mm	52°/6,750	
RAKES		52,73,733	
Vet rear disc brakes		•	
arking brake		•	
TEERING			
ydrostatic, with height and tilt adjustable steering column		•	
ITCH			
ategory		 	
lectrohydraulically controlled rear hitch ear hitch lift capacity	la la	10,500	
lechanical front hitch with retractable coupling bars	kg	0	
YDRAULIC SYSTEM			
ump output (std)	l/min	120	
losed centre hydraulic system (Load Sensing)		•	
ectronic distributor control		•	
ear auxiliary distributors	No. of ways	4	
ow regulator and timer		•	
RIVING POSITION			
lultifunction armrest		•	
ab		•	
/ork Display		•	
erformance Monitor		•	
omfortip		•	
igh visibility roof ab air suspension		•	
ab air suspension r conditioning		•	
MENSIONS AND WEIGHTS			
/ith front tyres		600/65R34"	
ith rear tyres		650/65R42"	
		3,095	
/heelbase	mm		
	mm mm	5209-5399	
ength (min-max)		5209-5399 3265-3270	
ength (min-max) eight (min-max) /idth (min-max)	mm		
Wheelbase length (min-max) Height (min-max) Width (min-max) Ground clearance (min-max) Total unladen weight (min-max)	mm mm	3265-3270	

STD ● OPT ○

Weight with cab (min-max)

Dealer



Use of original lubricants and coolants is recommended.

DEUTZ-FAHR is a brand of **8 SAME DEUTZ-FAHR** deutz-fahr.com



9,430-10,435